



ConTec SD-205CA

DESCRIPTION

ConTec SD-205CA is a unique blend of dispersing aids bringing calcium naphthalene sulfonate technology to a new level. It's highly active formulation improves both cement and color pigment efficiency in all types of architectural concrete. SD-205CA will also improve cement hydration and therefore provide higher compressive strength in manufactured concrete products.

APPLICATION

Use **ConTec SD-205CA** in all types of manufactured concrete where improved cement and pigment dispersion is desired. SD-205CA is a low viscosity liquid ready to use as received.

PACKAGING

ConTec SD-205CA is available in bulk quantities or packaged in 55 gallon (208 L) drums weighing 570 lbs (259 kg) and 260 gallon (984 L) totes weighing 2750 lbs (1247 kg).

TYPICAL PROPERTIES

Specific Gravity at 77F.....	1.2 - 1.22
Viscosity at 77F, cps	50—100
Weight per gallon	10.0
% Volatile matter (NVM(1))	~ 55

FEATURES / BENEFITS

- Improves cement particle dispersion and hydration.
- Aids pigment particle dispersion improving color development.
- Increases compressive and flexural strength.
- Proper use can potentially reduce cement and pigment usage.
- Improves the compaction process enhancing finished density.

HANDLING / STORAGE

ConTec SD-205CA should be stored at temperatures above 35°F (2°C). Care should be taken to prevent this product from freezing. Should SD-205CA freeze, warm till completely liquid then use mechanical agitation to reconstitute.

ADDITION RATES

The recommended dosage is 0.2% by weight of cement. In dry-cast concrete products SD-205CA will increase the demand for water by 5 to 10% above normal addition rates. SD-205CA is not a water reducer and should not be utilized as such. Please consult an ICT representative for further recommendations to determine the proper dosage rate and order of addition for your particular process. Order of addition procedures can vary per facility. Never mix SD-205CA with other admixtures before application.

The information contained herein is based on data believed by Innovative Concrete Technology, LLC, to be accurate, but we do not assume any liability for the accuracy of this information. All materials may present an unknown health and safety hazard. We neither suggest nor guarantee that any hazards mentioned are the only ones that exist. Anyone intending to rely on any recommendation or to use any equipment, technique, or material mentioned should also satisfy himself that he can meet all applicable safety and health standards. Determination of the suitability of any information or product for the use contemplated by any user, the manner of that use is the sole responsibility of the user.

Innovative Concrete Technology, LLC

Two Wall Street – Oxford, NJ 07863 • Ph. 908-453-2737 • Fax 908-453-3634