ConTec CS-670WS



DESCRIPTION

ConTec CS-670WS sealer is an aqueous fine particle dispersion of acrylic polymer. It is formulated to provide concrete masonry products with tough, water-resistant properties. ConTec CS-670WS is proven effective on porous concrete surfaces and can be applied in-line at the factory (wet side or dry side) or in the field.

APPLICATION

PACKAGING

ConTec CS-670WS is available in tote and drum quantities.

TYPICAL PROPERTIES

Form	White Liquid
Viscosity at 77°F, cps	<400
Density (lb./gal.)	8.7
Volatile Matter, % NVM(1)	Approx. 50
VOCs (lbs./gal)	0

FEATURES / BENEFITS

- Deep penetrating action
- Fast drying for reduced blocking
- Reduces efflorescence potential
- Non-yellowing and blush resistant
- Improves durability/chemical resistance
- Convenient concentrated formula
- Versatile wet or dry side application

HANDLING / STORAGE

ConTec CS-670WS can be stored over a wide range of temperatures but must be protected from freezing. If allowed to freeze, ConTec CS-670WS is no longer useable. Provide adequate ventilation and avoid inhaling mist when applying.

APPLICATION RATES

ConTec CS-670WS application rates will vary from 100 to 420ft²/gal (2.5-10m²/L) depending on surface texture and other characteristics, performance requirements, and desired gloss level. For wet-side applications, apply only enough material to satisfy surface demand. Please consult an ICT representative for further recommendations and application guidelines.

The information contained herein is based on data believed by Innovative Concrete Technology, LLC. to be accurate, but we do not assume any liability for the accuracy of this information. All materials may present an unknown health and safety hazard. We neither suggest nor guarantee that any hazards mentioned are the only ones that exist. Anyone intending to rely on any recommendation or to use any equipment, technique, or material mentioned should also satisfy himself that he can meet all applicable safety and health standards. Determination of the suitability of any information or product for the use contemplated by any user, the manner of that use is the sole responsibility of the user.

Innovative Concrete Technology, LLC

bestadmix.com

92 Thomas Rd, Port Murray NJ 07865 • Ph. 908-453-2737 • Fax 908-453-3634