

ConTec EC-60



DESCRIPTION

ConTec EC-60 is a multi-benefit efflorescence-controlling and water repellent admixture for concrete masonry units, hardscapes, and concrete roofing tile. Used properly, this unique formula enhances concrete plasticity, increases cement and pigment efficiency, and can significantly reduce unit cost.

APPLICATION

ConTec EC-60 is recommended for use in the production of concrete block, SRWs, pavers, slabs, manufactured stone veneer, and ornamental cast stone.

PACKAGING

ConTec EC-60 is available in totes and drums. An ICT representative will determine the proper dispensing system for your operation.

TYPICAL PROPERTIES

Form.....Milky White Liquid
 Viscosity at 77°F, cps.....100-300
 Density (lb./gal.).....8.4

FEATURES / BENEFITS

- Improves material feed and compaction
- Increases density, compressive strength
- Reduces efflorescence potential
- Enhances overall color integrity
- Significantly reduces absorption
- Reduces friction and machine wear

HANDLING / STORAGE

ConTec EC-60 should be stored at temperatures above 40°F (4.5°C). Never allow it to freeze or **ConTec EC-60** will become unusable.

ADDITION RATES

ConTec EC-60 has a recommended dosage range of 8-18 oz/cwt (520-1175mL/100kg) of cementitious materials. Consult your ICT representative for recommendations and dosing guidelines per application. Never mix **ConTec EC-60** with other admixtures before using.

The information contained herein is based on data believed by Innovative Concrete Technology, LLC. to be accurate, but we do not assume any liability for the accuracy of this information. All materials may present an unknown health and safety hazard. We neither suggest nor guarantee that any hazards mentioned are the only ones that exist. Anyone intending to rely on any recommendation or to use any equipment, technique, or material mentioned should also satisfy himself that he can meet all applicable safety and health standards. Determination of the suitability of any information or product for the use contemplated by any user, the manner of that use is the sole responsibility of the user.

Innovative Concrete Technology, LLC

bestadmix.com

92 Thomas Rd, Port Murray NJ 07865 • Ph. 908-453-2737 • Fax 908-453-3634