

# ConTec RA-546



## DESCRIPTION

**ConTec RA-546** release agent is made from safe, low-VOC, renewable bio-oils. When properly applied, **ConTec RA-546** reduces bug-holes and will not stain or discolor formed concrete surfaces.

## APPLICATION

**ConTec RA-546** is used to prevent concrete from adhering to molds, forms, machine palettes, and mixers. Use in as-received condition – do not dilute. A low-pressure airless or HVLP sprayer is recommended. Do not over-apply or allow excess product to pool in molds as it can damage the concrete surface. **ConTec RA-546** is suitable for use with most molds and in-liner types, but compatibility testing before use is recommended.

## PACKAGING

**ConTec RS-546** is available in tote and drum quantities.

## TYPICAL PROPERTIES

Form.....Amber/Brown Liquid  
 Viscosity at 77°F, cps.....<100  
 Density (lb./gal.).....7.3  
 Volatile Matter, % NVM(1).....0

## FEATURES / BENEFITS

- Efficient release
- Minimizes surface defects
- Reduces concrete build up
- High cost-performance ratio
- Non-toxic and user-friendly
- Renewable, bio-sourced
- Biodegradable

## HANDLING / STORAGE

**ConTec RA-546** can be stored over a wide range of temperatures. Provide adequate ventilation and avoid inhaling mist when applying.

## APPLICATION RATES

**ConTec RA-546** should be applied at a rate of 1,500-3,000ft<sup>2</sup>/gal. (40-75m<sup>2</sup>/L). Please consult an ICT representative for further application guidelines.

The information contained herein is based on data believed by Innovative Concrete Technology, LLC. to be accurate, but we do not assume any liability for the accuracy of this information. All materials may present an unknown health and safety hazard. We neither suggest nor guarantee that any hazards mentioned are the only ones that exist. Anyone intending to rely on any recommendation or to use any equipment, technique, or material mentioned should also satisfy himself that he can meet all applicable safety and health standards. Determination of the suitability of any information or product for the use contemplated by any user, the manner of that use is the sole responsibility of the user.

**Innovative Concrete Technology, LLC**

bestadmix.com

92 Thomas Rd, Port Murray NJ 07865 • Ph. 908-453-2737 • Fax 908-453-3634