

ConTec SD-215C



DISPERSANTS / WATER REDUCERS

DESCRIPTION

ConTec SD-215C is a mid/high-range water reducing admixture based on cutting-edge polycarboxylate technology. Intended for use in wet-cast production, this highly active formula improves cement particle dispersion and overall efficiency. **ConTec SD-215C** wets out quickly to achieve targeted slumps with shorter mix cycles.

APPLICATION

ConTec SD-215C is ideally suited wet cast production where increased slump and ease of concrete placement is desired. **ConTec SD-215C** improves cement efficiency by dispersing cement agglomerations, reducing water demand, and increasing reactivity rate with water (hydration).

PACKAGING

ConTec SD-215C is available in tote and drum quantities. An ICT representative will determine the proper dispensing system for your operation.

TYPICAL PROPERTIES

Form.....Amber/Brown Liquid
 Viscosity at 77°F, cps.....<300
 Density (lb./gal.).....9.1

FEATURES / BENEFITS

- High activity, fast wetting formula
- Increases flow without adding water
- Increases density and overall strength
- Maintains performance w/less cement
- Eases concrete placement/consolidation

HANDLING / STORAGE

Store **ConTec SD-215C** at temperatures above 40°F (4.5°C). Never allow it to freeze or **ConTec SD-215C** will become unusable.

ADDITION RATES

ConTec SD-215C has a recommended dosage range of 2-6 oz/cwt (130-390mL/100kg) of cementitious materials. This is proportional to the targeted water-cement ratio. Consult your ICT representative for recommendations and dosing guidelines per application.

The information contained herein is based on data believed by Innovative Concrete Technology, LLC. to be accurate, but we do not assume any liability for the accuracy of this information. All materials may present an unknown health and safety hazard. We neither suggest nor guarantee that any hazards mentioned are the only ones that exist. Anyone intending to rely on any recommendation or to use any equipment, technique, or material mentioned should also satisfy himself that he can meet all applicable safety and health standards. Determination of the suitability of any information or product for the use contemplated by any user, the manner of that use is the sole responsibility of the user.

Innovative Concrete Technology, LLC

bestadmix.com

92 Thomas Rd, Port Murray NJ 07865 • Ph. 908-453-2737 • Fax 908-453-3634