ConTec TS-727P



DESCRIPTION

ConTec TS-727P was formulated to enhance the overall integrity of concrete masonry products while minimizing unit production cost. Used properly, this unique multi-benefit admixture enhances concrete plasticity, increases cement and pigment dispersion, and greatly reduces moisture intrusion.

APPLICATION

ConTec TS-727P is recommended for use in the production of pavers, SRWs, concrete block, manufactured stone veneer, and cast stone.

PACKAGING

ConTec TS-727P is available in totes and drums. An ICT representative will determine the proper dispensing system for your operation.

TYPICAL PROPERTIES

Form	Dark Brown Liquid
Color / Odor	Slight
Density (lb./gal)	9.0
pH	8 - 9

FEATURES / BENEFITS

- Improves product consistency
- Increases product density, strength
- Reduces efflorescence potential
- Increases freeze/thaw durability
- Enhances overall color integrity
- Significantly reduces absorption

HANDLING / STORAGE

ConTec TS-727P must be stored at moderate temperatures and away from direct sun. Never allow the product to freeze. When stored properly, ConTec TS-727P has a shelf life of 6 months. Avoid creating an aerosol or mist that could be inhaled.

ADDITION RATES

ConTec TS-727P has a recommended dosage range of 3-5 oz/cwt (195-325mL/100kg) of cementitious materials. Please consult your ICT technical representative for recommendations and guidelines by application.

The information contained herein is based on data believed by Innovative Concrete Technology, LLC. to be accurate, but we do not assume any liability for the accuracy of this information. All materials may present an unknown health and safety hazard. We neither suggest nor guarantee that any hazards mentioned are the only ones that exist. Anyone intending to rely on any recommendation or to use any equipment, technique, or material mentioned should also satisfy himself that he can meet all applicable safety and health standards. Determination of the suitability of any information or product for the use contemplated by any user, the manner of that use is the sole responsibility of the user.

Innovative Concrete Technology, LLC

info@bestadmix.com

92 Thomas Rd – Port Murray, NJ 07863 • Ph. 908-453-2737 • Fax 908-453-3634