

TechShield 833

DESCRIPTION

TechShield 833 liquid admixture was formulated to enhance the overall integrity of concrete masonry products while minimizing production cost. When used properly this unique admixture chemically reacts with cement and its water repellent components form a permanent bond within the concrete. This provides higher cement efficiency, enhanced efflorescence control, and long-lasting resistance to moisture ingress. **TechShield 833** is a **Tech Shield Water Repellent Admixture System** component for specified concrete masonry construction.

APPLICATION

TechShield 833 can be used in a wide variety of concrete masonry products and other cementitious applications. It is particularly useful where the use of conventional water repellants and efflorescence control agents have not been effective. When used in both CMU and masonry mortar **TechShield 833** protects exterior walls from water infiltration and moisture migration for the life of the structure.

ADDITION RATES

The typical dosage range for **TechShield 833** is 2-8 oz/cwt. Consult your ICT technical representative for recommendations and guidelines for your application

The information contained herein is based on data believed by Innovative Concrete Technology, LLC. to be accurate, but we do not assume any liability for the accuracy of this information. All materials may present an unknown health and safety hazard. We neither suggest nor guarantee that any hazards mentioned are the only ones that exist. Anyone intending to rely on any recommendation or to use any equipment, technique, or material mentioned should also satisfy himself that he can meet all applicable safety and health standards. Determination of the suitability of any information or product for the use contemplated by any user, the manner of that use is the sole responsibility of the user.

FEATURES / BENEFITS

- **Increases** strength at all ages
- **Enhances** color strength and brightness
- **Greatly** reduces efflorescence
- **Enhances** freeze/thaw durability
- **Increases** density
- **Provides** lasting water repellency

HANDLING / STORAGE

TechShield 833 must be stored at moderate temperatures and away from direct sun. Never allow to freeze. When stored properly, **TechShield 833** has a shelf life of 12 months. Avoid creating an aerosol or mist that could be inhaled.

PACKAGING

TechShield 833 is available in totes and drums. An ICT representative will determine the proper dispensing system to match your operation.

TYPICAL PROPERTIES

Form.....	Milky White Liquid
Color / Odor.....	Slight
Density (lb./gal).....	8.4
pH.....	8 - 9

Innovative Concrete Technology, LLC

info@bestadmix.com

92 Thomas Rd – Port Murray, NJ 07863 • Ph. 908-453-2737 • Fax 908-453-3634